

NEREA WALL MOUNT FAUCET

Cat. No.
203/59



Lavatory Faucet



Valve width : 8"
Spout reach: 7 3/4"
Holes to drill in wall: 1 1/4"

From center of feed to finished wall: 1 11/16" to 2 3/4"

-
- Cleaning and Care Instructions:
- We recommend you wipe your faucets dry after every use. This will prevent accumulation of mineral deposits left when water evaporates. Use a soft cloth for wiping all surfaces.
 - Avoid harsh and abrasive cleaners on all faucet surfaces. Use only a soft, damp cloth with mild liquid soap to clean the finished surfaces of all faucets, including coated polished brass, gold, brushed nickel, etc.
 - Painted and plated surfaces alike, should be coated regularly with a thin protective film. Non-abrasive liquid car wax is recommended.
-

Dimensions and specifications subject to change without notice.

Features

- ▶ All brass construction
- ▶ Ceramic quarter turn disc cartridges
- ▶ Rough in valve includes reversible fittings for sweat or threaded water connection
- ▶ Includes open grid drain
- ▶ 25 year limited warranty on mechanical components
- ▶ 7 year warranty on finishes

Finishes

CR Chrome

Compliance Certification:
Meets or exceeds the following specifications:
ASME A112.18.1-2003

.....
We recommend that you check all water connections for leaks before closing the wall.
.....

