

DENISSE THERMOSTATIC MIXER VALVE & TRIM

Cat. No.
U216.01/64



Thermostatic Mixer Valve & Trim



Faceplate: 6 3/8"
Hole in wall for valve: 2"

Features

- ▶ All brass construction
- ▶ Easy to replace cartridge
- ▶ Flow rate 5.3 GPM @ 45 PSI
- ▶ Safety of scald guard operation
- ▶ 25 year limited warranty on mechanical components
- ▶ 7 year warranty on finishes
- ▶ IAPMO approved

Finishes

CR Chrome
PE Brushed Nickel

Compliance Certification:

Meets or exceeds the following specifications:
ASME A112.18.1-2003

We recommend that you check all water connections for leaks before closing the wall.

Cleaning and Care Instructions:

We recommend you wipe your faucets dry after every use. This will prevent accumulation of mineral deposits left when water evaporates. Use a soft cloth for wiping all surfaces.

Avoid harsh and abrasive cleaners on all faucet surfaces. Use only a soft, damp cloth with mild liquid soap to clean the finished surfaces of all faucets, including coated polished brass, gold, brushed nickel, etc.

Painted and plated surfaces alike, should be coated regularly with a thin protective film. Non-abrasive liquid car wax is recommended.

Dimensions and specifications subject to change without notice.

